





**safetoe**  
 TOP QUALITY SINCE 1984  
 Top Quality  
 Creative Design  
 Amazing Comfort  
 ★★★★★  
 Keep Worker in Safe!

# M-8553 New S3 SRC

## Women Safety Shoes

Upper : Full Grain Cow Nubuck Leather  
 Lining : Sanvlar-tex Waterproof Membrane  
 Insole : Comfortable Hi-Polyu Insoles  
 Outsole : PU/PU Injection (Desma Injection)  
 Toecap : Steel Toecap  
 Penetration : Kevlar Midsole Plate  
 Size : EU 37-47#, UK 3-13#, USA-14#  
 CE EN ISO 20345:2011 S3 SRC & ASTM F2413-18 M I/75 C/75 PR  
 Application : Construction, Logistics, Mechanics, Glasses Installation, Workshop, Oil & Gas, Chemical Factory etc



### Steel Toecap Protection • AN1-EN12568

Stainless steel toe cap can reach 200 joules from falling or rolling objects. It is stronger than iron toe cap.



### Kevlar Plate Protection • AN1-EN12568

Kevlar midsole plate, is zero-penetration resistant. It can resist 1100 newtons nail puncture from sharp objects. It is stronger and more flexible than steel plate.



### Brown Cow Nubuck Leather Upper • CE EN ISO 20345:2011

High quality full grain cow nubuck leather with thickness 1.6-1.8mm. It is treated with breathable technology to keep feet from dry during walking all days. Tear strength is required 10% higher than Europe test requirement, to reach longer lifespan.



### Heavy Duty PU/PU Outsole • CE EN ISO 20345:2011

The outsole is manufactured with Germany Fully-Automatic Injection Technology. The midsole is 45±5 degree hardness PU, which is soft and shock absorption. The outsole is 65±5 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

## Sole Bonding Strength Test

- EN ISO 20344:2011, 5.2 (Between Upper & Sole)
- Average Test Result  $5.8 \pm 5$  (N/mm)



### Upper, Lining & Bonding Strength Test Result

Leather Tear Strength $\geq$	120.0 Newtons
Leather Tensile Properties $\geq$	15.0 N/mm <sup>2</sup>
Lining Tear Strength $\geq$	15.0 N/mm
Bonding Strength $\geq$	4.0 N/mm

✓ Protection With Slip Resistant (SRC)	Result
Test Requirement : SRA (Eurotile 2+Nal S) Forward Heel Slip $\geq 0.28$ & Forward Flat Slip: $\geq 0.32$ SRB (Steel Floor+Glycerine) Forward Heel Slip $\geq 0.13$ & Forward Flat Slip: $\geq 0.18$	PASS
Standards : EN ISO20344:2011(5.11) , SRC Means both SRA & SRB requirements are fulfilled.	
✓ Protection With Anti-Static	Result
Test Requirement : Anti-static 100K $\Omega$ -1000M $\Omega$ , Test Voltage: 100 $\pm$ 2 V DC, Test Period: 1 Minute	PASS
Standards : EN ISO 20344:2011(5.10) Dry Humidity (30 $\pm$ 5) & Wet Humidity (85 $\pm$ 5)	
✓ Protection Resistant to Fuel Oil	Result
Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(*)	PASS
Standards : EN ISO 20344:2011(8.6.1)	
SAFETOE Standard Package Instruction (Average 38# for Reference)	
Shoes Weight : 850-950 Grams /Pair	Carton Weight : 10-11 KGS /Carton
1 Pair / Color Box , Dimensions : 30 $\times$ 22 $\times$ 11CM	10 Pair / Carton , Dimensions : 57 $\times$ 45 $\times$ 31CM



### User Instructions:

- 1.) RECOMMENDED TO USE : Construction, Logistics, Mechanics, Glasses Installation, Workshop, Farming, Garden, Oil & Gas, Chemical Factory etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

- 4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.
- 5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.